

US009411009B1

US 9,411,009 B1

Aug. 9, 2016

(12) United States Patent

Aguayo Gonzalez et al.

(54) SYSTEMS, METHODS, AND APPARATUSES FOR INTRUSION DETECTION AND ANALYTICS USING POWER CHARACTERISTICS SUCH AS SIDE-CHANNEL INFORMATION COLLECTION

(71) Applicant: **POWER FINGERPRINTING INC.**,

Vienna, VA (US)

(72) Inventors: Carlos R. Aguayo Gonzalez, Reston,

VA (US); **Jeffrey H. Reed**, Blacksburg, VA (US); **Steven C. Chen**, Potomac,

MD (US)

(73) Assignee: **Power Fingerprinting Inc.**, Vienna, VA

(US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 14/881,862

(22) Filed: Oct. 13, 2015

Related U.S. Application Data

- (62) Division of application No. 14/720,497, filed on May 22, 2015, now Pat. No. 9,268,938.
- (51) **Int. Cl.** *G01R 31/00* (2006.01) *G01R 31/28* (2006.01)
 (Continued)
- (58) Field of Classification Search

See application file for complete search history.

(10) **Patent No.:**

(56)

(45) Date of Patent:

References Cited U.S. PATENT DOCUMENTS

7,515,094 B2 4/2009 Keller, III 7,853,437 B2 12/2010 Seguin et al. (Continued)

FOREIGN PATENT DOCUMENTS

WO WO2010/044069 4/2010 WO WO2013/131073 9/2013 WO 2014/144857 A2 9/2014

OTHER PUBLICATIONS

Cardoso, Bill et al., "X-Ray Inspection Techniques to Identify Counterfeit Electronic Components", ECN Magazine, Mar. 11, 2014, 6 pgs., Downloaded on Nov. 11, 2015 at http://www.ecnmag.com/articles/2014/03/x-ray-inspection-techniques-identify-counterfeit-electronic-components.

(Continued)

Primary Examiner — Jermele M Hollington Assistant Examiner — Raul Rios Russo (74) Attorney, Agent, or Firm — Cooley LLP

(57) ABSTRACT

Some embodiments described herein include a system that collects and learns reference side-channel normal activity, process it to reveal key features, compares subsequent collected data and processed data for anomalous behavior, and reports such behavior to a management center where this information is displayed and predefine actions can be executed when anomalous behavior is observed. In some instances, a physical side channel (e.g. and indirect measure of program execution such as power consumption or electromagnetic emissions and other physical signals) can be used to assess the execution status in a processor or digital circuit using an external monitor and detect, with extreme accuracy, when an unauthorized execution has managed to disrupt the normal operation of a target system (e.g., a computer system, etc.).

19 Claims, 19 Drawing Sheets

